

## **ACD-220**

## WIRELESS CURTAIN DETECTOR

ACD–220 is a wireless curtain motion detector. ACD–220 is designed for indoor use. The detector operates within the ABAX 2 two-way wireless system.

The device is operated by:

- ACU-220/ACU-280 system controller
- ARU-200 signal retransmitter

ACD–220 is available in three colour options: white (ACD–220), brown (ACD–220 BR) and dark grey (ACD–220 DG).

- motion detection using a passive infrared sensor (PIR)
- adjustable sensitivity of motion detection
- digital algorithm of motion detection
- digital temperature compensation
- lens designed specifically for SATEL short range curtain detectors
- encrypted two-way radio communication in the 868 MHz frequency band (AES standard)
- diversification of transmission channels 4 channels allow automatic selection of one that guarantees transmission without interference with other signals in the 868 MHz frequency band
- remote detector firmware update
- remote configuration
- built-in temperature sensor (temperature measurement from -10 °C to +55 °C)
- LED indicator
- monitoring of motion detection system
- ECO option to extend battery life
- battery check
- tamper protection against opening the enclosure and against detaching it from mounting surface



## **TECHNICAL DATA**

Battery working time (in years)	up to 2
Detected target velocity	0,31 m/s
Operating temperature range	-10°C+55°C
Max. current consumption	15 mA
Weight	43 g
Maximum humidity	93±3%
Operating frequency band	868,0 ÷ 868,6 MHz
Battery	CR123A 3V
Standby current consumption	70 µA
Dimensions	20 x 102 x 25 mm
Environmental class according to EN50130-5	
Complied with standards	EN 50130-4, EN 50130-5
Temperature measurement accuracy	±1°C
Warm-up period	5s
Radio communication range (in open area) for ACU-220	up to 2000 m
Radio communication range (in open area) for ACU-280	up to 1200 m
Temperature measurement range	-10°C+55°C
Detection area	5 m x 1 m, 15°