

INT-KSG-B

TOUCH KEYPAD

The touch keypad **INT-KSG** does not only stand for attractive design, but also for simplification for the daily operation of advanced alarm systems and home automation using the functionalities of the **INTEGRA** control units. With the **MACRO** functions, a whole sequence of actions can be performed through a single command. This way, it can be used e.g. for extended light scenes.

- large, easily readable LCD displaying detailed information on system state
- keypad backlight to allow the use in dark rooms
- new user interface that makes everyday use easier
- customizable standby screen
- installer defined 4 menus (16 items each) and quick access functions
- **MACRO** feature that activates sequence of actions with a single key
- individual keypress feedback with LED and beep
- LED system state indicators
- **PANIC**, **FIRE** and **AUX** alarms dedicated triggering keys
- audible indication of system events
- 2 zones expansion
- indication of loss of communication with panel
- available in white (**INT-KSG-W**) and black (**INT-KSG-B**)



TECHNICAL DATA

| | |
|---|-------------------|
| Supply voltage | 12 V DC |
| Operating temperature range | -10°C...+55°C |
| Standby mode current consumption | 165 mA |
| Max. current consumption | 175 mA |
| Weight | 320 g |
| Maximum humidity | 93±3% |
| Environmental class according to EN50130-5 | II |
| Enclosure dimensions (width x height x thickness) | 143 x 156 x 22 mm |